

1. All work shall conform to the requirements of Section 600 of the "Idaho Standards for Public Works Construction" (ISPMC) and the City of Coeur d'Alene Standard Drawings and Specifications. In the case of conflict, City of Coeur d'Alene Standards shall prevail.
2. Location and elevation of existing facilities should be confirmed by field measurements and excavation exploration by the contractor, prior to beginning of new work.
3. Stormwater Division does not respond to "One-Call" notification. They must be called separately for locates on Storm Drain.
4. The contractor must secure approval from the City of Coeur d'Alene Engineering Inspector prior to backfill over Storm Drain mainline.
5. The City of Coeur d'Alene Engineering Inspector shall be notified at least forty-eight (48) hours prior to commencing work on Storm Drains.
6. All public Storm Drain lines shall be videotaped and submitted to the City of Coeur d'Alene Stormwater Division offices for review and approval prior to paving. Please allow forty-eight (48) hours for review.
7. All manholes, drywells, and catch basins shall be inspected twice by the City of Coeur d'Alene Engineering Inspector - prior to backfill and prior to acceptance of improvements. Call 769-2285 for inspection scheduling.

REVISION	APPROVED	DATE	CITY OF COEUR D'ALENE STANDARD DRAWING	APPROVED BY:	DATE:
			STORM SYSTEM NOTES	 CITY ENGINEER, PE 7432	4/1/08
				DWG NO.	M-33