

1. All work shall conform to the "Idaho Standards for Public Works Construction" and the City of Coeur d'Alene Standard Drawings and Specifications. In the case of a conflict, City of Coeur d'Alene Standards shall prevail.

2. The contractor shall notify the appropriate utility company prior to starting work near any facilities and shall coordinate his work with company representatives. All utility services shall be installed underground, for existing utility locations, contact "call before you dig" at *811 at least 48 hours prior to starting any excavations.

3. Work shall not begin until a notice to proceed is issued by the City.

4. The contractor shall notify the City of Coeur d'Alene Streets & Engineering Inspector 48 hours prior to starting work.

5. An encroachment permit shall be obtained from the City Streets & Engineering Department for work within existing City right-of-way.

6. The contractor shall have an approved set of improvement plans on the job site at all times.

7. Construction expansion joints are required in curb and gutter at returns and at driveway intersections per City Standards. Weakened plane joints are required every twentyfive (25) feet per City Standards.

8. All underground utility laterals shall be installed before construction of curbs, cross gutters, or surfacing of the streets.

9. Where trenches are within public easements, compaction test results shall be submitted to the Engineer of work and the City Engineer by a qualified engineer which certify that trench backfill was compacted as required in accordance with ISPWC and City of Coeur d'Alene Specifications.

10. All testing required by the City of Coeur d'Alene shall be at no cost to the City.



CITY OF COEUR D'ALENE STANDARD DRAWING

GENERAL NOTES
PAGE 1

APPROVED BY:

Chris Bosley
CITY ENGINEER, PE 10804

10/1/24
DATE:

DWG NO.

M-22